

NC DWELL

SPECIFICATION

Product model	NC-003103RH-60	
Product Size (mm)	Φ145*600 mm	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP54
	Impact Strength(IK)	/
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	1.99 Kg
	Rated Power	9
	LED Module Rated Power	8W*1
	Input Voltage	220V
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	39 lm/W
	Imax(cd)	248 cd
	Luminaire Efficiency(LOR%)	44
	Total Flux	359 lm
	Beam angle(At 50% of Imax)	127°
	Energy Efficiency Index(EEI)	0.14
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000K
	SCDM	≤5
	Surge transient protection	/
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	CREE
	LED Model No.	1304
	LED Nominal Flux(lm)	800 lm
	LED Quantity	1
Driver	STOCK NUMBER	L-QD-PA137
	Driver Output	27-40VDC
	Driver Efficiency	≥81%
	Power Factor	≥0.9
	THD	≤16%
	Ripple current	≤20%
Certification	CE, CCC, CB, EAC, SAA, BIS	

