

NC DWELL

SPECIFICATION

Product model	NC-003336	
Product Size (mm)	65*73*150mm	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	/
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	0.50 Kg
	Rated Power	7 W
	LED Module Rated Power	6W*1
	Input Voltage	100-240V~
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	94 lm/W
	Imax(cd)	1772 cd
	Luminaire Efficiency(LOR%)	81
	Total Flux	634 lm
	Beam angle(At 50% of Imax)	189°
	Energy Efficiency Index(EEI)	0.19
	Colour rendering index(Ra)	≥80
Colour Temperature(CCT)	3000K	
SDCM	≤5	
Surge transient protection	/	
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	SEOUL
	LED Model No.	5050
	LED Nominal Flux(lm)	390 lm
	LED Quantity	2
Driver	STOCK NUMBER	L-QD-PA146
	Driver Output	12-20VDC
	Driver Efficiency	≥75%
	Power Factor	≥0.45
	THD	/
	Ripple current	≤30%
Certification	CE, CCC, CB, EAC, SAA, BIS	

