

NC DWELL

SPECIFICATION

Product model	NC-803482	
Product Size (mm)	170*118*220	
Product description	Body material	Die Casting Aluminum
	Optical cover material	PC
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	1.98 Kg
	Rated Power	28 W
	LED Module Rated Power	12W*2
	Input Voltage	220V
	Frequency Range	50/60Hz
	Luminaire luminous efficiency(EFF)	83 lm/W
	Imax(cd)	2263 cd
	Luminaire Efficiency(LOR%)	93
	Total Flux	2349 lm
	Beam angle(At 50% of Imax)	199°
	Energy Efficiency Index(EEI)	0.30
	Colour rendering index(Ra)	≥80
Colour Temperature(CCT)	3000 K	
SCDM	≤5	
Surge transient protection		
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	CREE
	LED Model No.	1507
	LED Nominal Flux(lm)	1260 lm
	LED Quantity	2
Driver	STOCK NUMBER	L-QD-PA160
	Driver Output	27-40VDC
	Driver Efficiency	≥81%
	Power Factor	≥0.9
	THD	≤10%
	Ripple current	≤15%
Certification	CE, CCC, CB, EAC, SAA, BIS	

