

NC DWELL

SPECIFICATION

Product model	NC-033231-80	
Product Size (mm)	108*120*800	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	IK08
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	2.33 Kg
	Rated Power	13 W
	LED Module Rated Power	12W*1
	Input Voltage	100-240V~
	Frequency Range	50/60Hz
	Luminaire luminous efficiency(EFF)	47 lm/W
	Imax(cd)	415 cd
	Luminaire Efficiency(LOR%)	48
	Total Flux	613 lm
	Beam angle(At 50% of Imax)	180°
	Energy Efficiency Index(EEI)	0.25
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000 K
	SCDM	≤5
Surge transient protection	/	
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	CREE
	LED Model No.	1507
	LED Nominal Flux(lm)	1260 lm
	LED Quantity	1 PCS
Driver	STOCK NUMBER	L-QD-PA136
	Driver Output	27-40VDC
	Driver Efficiency	≥81%
	Power Factor	≥0.85
	THD	≤10%
	Ripple current	≤15%
Certification	CE, CCC, CB, EAC, SAA, BIS	

