

NC DWELL

SPECIFICATION

| | | |
|-----------------------------------|---|--------------------------|
| Product model | NC-803093 | |
| Product Size (mm) | Ø108*165*260mm | |
| Product description | Body material | Die Casting Aluminum |
| | Optical cover material | |
| | Surface finish | Polyester powder coating |
| | Safety | CLASS I |
| | Protection Grade | IP65 |
| | Impact Strength(IK) | |
| | UV-Resistant | F1 |
| | Life Span | 50000 Hrs |
| | Net Weight | 1.64 |
| | Rated Power | 28 W |
| | LED Module Rated Power | 12W*2 |
| | Input Voltage | 220V |
| | Frequency Range | 50/60 Hz |
| | Luminaire luminous efficiency(EFF) | 71 lm/W |
| | Imax(cd) | 1964 cd |
| | Luminaire Efficiency(LOR%) | 79 |
| | Total Flux | 1998 lm |
| | Beam angle(At 50% of Imax) | 197° |
| | Energy Efficiency Index(EEI) | 0.30 |
| | Colour rendering index(Ra) | ≥80 |
| Colour Temperature(CCT) | 3000K | |
| SCDM | ≤5 | |
| Surge transient protection | / | |
| Working temperature | -30°C ~ +45°C | |
| LED Chip | LED Brand | CREE |
| | LED Model No. | 1507 |
| | LED Nominal Flux(lm) | 1260 lm |
| | LED Quantity | 2 |
| Driver | STOCK NUMBER | L-QD-PA160 |
| | Driver Output | 27-40VDC |
| | Driver Efficiency | ≥81% |
| | Power Factor | ≥0.9 |
| | THD | ≤10% |
| | Ripple current | ≤15% |
| Certification | CE, CCC, CB, EAC, SAA, BIS | |

