

NC DWELL

SPECIFICATION

Product model	NC-033072	
Product Size (mm)	Φ90*113	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	/
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	0.56 Kg
	Rated Power	7W
	LED Module Rated Power	6W*1
	Input Voltage	100-240V~
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	69 lm/W
	Imax(cd)	792 cd
	Luminaire Efficiency(LOR%)	72
	Total Flux	476 lm
	Beam angle(At 50% of Imax)	38°
	Energy Efficiency Index(EEI)	0.13
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000K
SCDM	≤5	
Surge transient protection	/	
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	CREE
	LED Model No.	1304
	LED Nominal Flux(lm)	660 lm
	LED Quantity	1 PCS
Driver	STOCK NUMBER	L-QD-PA133
	Driver Output	27-42VDC
	Driver Efficiency	≥78%
	Power Factor	≥0.45
	THD	/
	Ripple current	≤30%
Certification	CE, CCC, CB, EAC, SAA, BIS	

