

NC DWELL

SPECIFICATION

Product model	NC-133243	
Product Size (mm)	Ø171*76	
Product description	Body material	Die Casting Aluminum
	Optical cover material	
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	0.74
	Rated Power	6 W
	LED Module Rated Power	0.25W*24
	Input Voltage	220V
	Frequency Range	50/60Hz
	Luminaire luminous efficiency(EFF)	53 lm/W
	Imax(cd)	115 cd
	Luminaire Efficiency(LOR%)	38
	Total Flux	344 lm
	Beam angle(At 50% of Imax)	117 , 120
	Energy Efficiency Index(EEI)	0.83
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000 K
SCDM	≤5	
Surge transient protection		
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	OSRAM
	LED Model No.	2835
	LED Nominal Flux(lm)	37.5 lm
	LED Quantity	24 PCS
Driver	STOCK NUMBER	L-QD-PA133
	Driver Output	27-42VDC
	Driver Efficiency	≥78%
	Power Factor	≥0.45
	THD	/
	Ripple current	≤30%
Certification	CE, CCC, CB, EAC, SAA, BIS	

