



Product model	NC-003032	
Product Size (mm)	88*78*124	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	/
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	0.49
	Rated Power	7 W
	LED Module Rated Power	3W*2
	Input Voltage	100-240V~
	Frequency Range	50/60Hz
	Luminaire luminous efficiency(EFF)	66 lm/W
	Imax(cd)	158 cd
	Luminaire Efficiency(LOR%)	55
	Total Flux	433 lm
	Beam angle(At 50% of Imax)	215°
	Energy Efficiency Index(EEI)	0.19
	Colour rendering index(Ra)	≥80
Colour Temperature(CCT)	3000 K	
SDCM	≤5	
Surge transient protection	/	
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	SEOUL
	LED Model No.	5050
	LED Nominal Flux(lm)	390 lm
	LED Quantity	2 PCS
Driver	STOCK NUMBER	L-QD-PA108
	Driver Output	6-8VDC
	Driver Efficiency	≥57%
	Power Factor	≥0.45
	THD	/
	Ripple current	≤30%
Certification	CE, CCC, CB, EAC, SAA, BIS	