

NC DWELL

SPECIFICATION

| | | |
|-----------------------------------|---|--------------------------|
| Product model | NC-133244 | |
| Product Size (mm) | 171*171*71 | |
| Product description | Body material | Die Casting Aluminum |
| | Optical cover material | |
| | Surface finish | Polyester powder coating |
| | Safety | CLASS I |
| | Protection Grade | IP65 |
| | Impact Strength(IK) | |
| | UV-Resistant | F1 |
| | Life Span | 50000 Hrs |
| | Net Weight | 0.82 |
| | Rated Power | 6 W |
| | LED Module Rated Power | 0.25W*24 |
| | Input Voltage | 220V |
| | Frequency Range | 50/60Hz |
| | Luminaire luminous efficiency(EFF) | 52 lm/W |
| | Imax(cd) | 109 cd |
| | Luminaire Efficiency(LOR%) | 38 |
| | Total Flux | 344 lm |
| | Beam angle(At 50% of Imax) | 131 , 134 |
| | Energy Efficiency Index(EEI) | 0.83 |
| | Colour rendering index(Ra) | ≥80 |
| Colour Temperature(CCT) | 3000 K | |
| SCDM | ≤5 | |
| Surge transient protection | | |
| Working temperature | -30°C ~ +45°C | |
| LED Chip | LED Brand | OSRAM |
| | LED Model No. | 2835 |
| | LED Nominal Flux(lm) | 37.5 lm |
| | LED Quantity | 24 PCS |
| Driver | STOCK NUMBER | L-QD-PA133 |
| | Driver Output | 27-42VDC |
| | Driver Efficiency | ≥78% |
| | Power Factor | ≥0.45 |
| | THD | / |
| | Ripple current | ≤30% |
| Certification | CE, CCC, CB, EAC, SAA, BIS | |

