

NC DWELL

SPECIFICATION

Product model	NC-003059	
Product Size (mm)	100*100*100mm	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	IK06
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	0.67 Kg
	Rated Power	6W
	LED Module Rated Power	3W*2
	Input Voltage	100-240V~
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	51 lm/W
	Imax(cd)	78 cd
	Luminaire Efficiency(LOR%)	43
	Total Flux	302 lm
	Beam angle(At 50% of Imax)	88°
	Energy Efficiency Index(EEI)	0.18
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000K
	SDCM	≤5
	Surge transient protection	/
	Working temperature	-30°C ~ +45°C
LED Chip	LED Brand	CREE
	LED Model No.	XTE3535
	LED Nominal Flux(lm)	345 lm
	LED Quantity	2 PCS
Driver	STOCK NUMBER	L-QD-PA108
	Driver Output	6-8VDC
	Driver Efficiency	≥57%
	Power Factor	≥0.45
	THD	/
	Ripple current	≤30%
Certification	CE, CCC, CB, EAC, SAA, BIS	

