

NC DWELL

SPECIFICATION

| | | |
|-----------------------------------|---|--------------------------|
| Product model | NC-013102RH-60 | |
| Product Size (mm) | Φ145*600 mm | |
| Product description | Body material | Die Casting Aluminum |
| | Optical cover material | / |
| | Surface finish | Polyester powder coating |
| | Safety | CLASS I |
| | Protection Grade | IP54 |
| | Impact Strength(IK) | IK08 |
| | UV-Resistant | F1 |
| | Life Span | 50000 Hrs |
| | Net Weight | 1.82 Kg |
| | Rated Power | 9 |
| | LED Module Rated Power | 8W*1 |
| | Input Voltage | 220V |
| | Frequency Range | 50/60 Hz |
| | Luminaire luminous efficiency(EFF) | 60 lm/W |
| | Imax(cd) | 274 cd |
| | Luminaire Efficiency(LOR%) | 69 |
| | Total Flux | 555 lm |
| | Beam angle(At 50% of Imax) | 116° |
| | Energy Efficiency Index(EEI) | 0.14 |
| | Colour rendering index(Ra) | ≥80 |
| Colour Temperature(CCT) | 3000K | |
| SCDM | ≤5 | |
| Surge transient protection | / | |
| Working temperature | -30°C ~ +45°C | |
| LED Chip | LED Brand | CREE |
| | LED Model No. | 1304 |
| | LED Nominal Flux(lm) | 800 lm |
| | LED Quantity | 1 |
| Driver | STOCK NUMBER | L-QD-PA137 |
| | Driver Output | 27-40VDC |
| | Driver Efficiency | ≥81% |
| | Power Factor | ≥0.9 |
| | THD | ≤16% |
| | Ripple current | ≤20% |
| Certification | CE, CCC, CB, EAC, SAA, BIS | |

