

NC DWELL

SPECIFICATION

Product model	NC-803472	
Product Size (mm)	133*86*180	
Product description	Body material	Die Casting Aluminum
	Optical cover material	PC
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	1.17 Kg
	Rated Power	13 W
	LED Module Rated Power	6W*2
	Input Voltage	220V
	Frequency Range	50/60Hz
	Luminaire luminous efficiency(EFF)	58 lm/W
	Imax(cd)	808cd
	Luminaire Efficiency(LOR%)	55
	Total Flux	737 lm
	Beam angle(At 50% of Imax)	195°
	Energy Efficiency Index(EEI)	0.24
	Colour rendering index(Ra)	≥80
Colour Temperature(CCT)	3000 K	
SCDM	≤5	
Surge transient protection		
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	CREE
	LED Model No.	1304
	LED Nominal Flux(lm)	660 lm
	LED Quantity	2
Driver	STOCK NUMBER	L-QD-PA136
	Driver Output	27-40VDC
	Driver Efficiency	≥81%
	Power Factor	≥0.85
	THD	≤10%
	Ripple current	≤15%
Certification	CE, CCC, CB, EAC, SAA, BIS	

