

NC DWELL

SPECIFICATION

Product model	NC-113104-60	
Product Size (mm)	112*112*600mm	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP54
	Impact Strength(IK)	IK08
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	1.60 Kg
	Rated Power	6.8 W
	LED Module Rated Power	6W*1
	Input Voltage	220-240V ~
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	67 lm/W
	Imax(cd)	235 cd
	Luminaire Efficiency(LOR%)	56
	Total Flux	454 lm
	Beam angle(At 50% of Imax)	180°
	Energy Efficiency Index(EEI)	0.17
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000K
	SDCM	≤5
	Surge transient protection	L/N:2KV
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	CREE
	LED Model No.	1304
	LED Nominal Flux(lm)	660 lm
	LED Quantity	1
Driver	STOCK NUMBER	L-QD-PA253
	Driver Output	27-42VDC
	Driver Efficiency	≥81%
	Power Factor	≥0.65
	THD	/
	Ripple current	≤30%
Certification	CE, CCC, CB, EAC, SAA, BIS	

