

Norfolk Pillar Lantern



Stock Code: NR4 BLK

Pillar

Product Description

A full range of leaded lanterns, the Norfolk is a versatile choice for all residential applications. Offering unique styling and exceptional value, each lantern panel features five separate pieces of glass, hand-leaded together. All versions are backed by a 5 year anti-corrosion guarantee. The NR1 is available with a P.I.R. detector which is guaranteed for 2 years. Available in a Black finish. Corner bracket C/BKT5 is available for wall models.

Product Attributes







- Weight: 2.1 kg
- Fitting Height: 1090mm
- Width/Diameter: 184mm
- Base Plate Width: 140mm
- Finish: Black
- Build Materials: Metal, Glass
- Max Wattage: 1 x 100W E27
- Voltage: 220-240v 50hz
- Number of lamps: One
- Bulb Included: No
- IP Rating: IP43
- Class I/II: Class I
- Product Type: Pillar Lantern
- Box Dimensions: 23.5x20x34cm
- Barcode: EAN 5024005415107
- Anti-corrosion guarantee: 5 years
- Family: Norfolk

ORDER OF ASSEMBLY A ~ B ~ C ~ D





1 Before starting the electrical work or connecting your light you will need to switch off your power supply at the fuse box (consumer unit). Either the miniature circuit breaker (MCB) can be turned off for the circuit for your light and applying **RED** insulating tape over the MCB to prevent it from being accidentally turned on. Or the main switch can be turned off, the circuit fuse removed, and the main switch turned on again to restore power to the rest of the house.


2 Colour code for fixed wiring:

GREEN/YELLOW	- Earth	
BROWN	- Live	
BLUE	- Neutral	
BLUE with brown sleeving	- Switch wire with sleeving	
Live wires can also sometimes be signified by a RED wire		
Neutral wires and also sometimes be signified by a white or black wire		


NOTE: Some luminaires may have a clear cable. In this case, the earth wire will be marked with a green/yellow thread.

3 CLASS I Luminaires (Earthed) - Connect the brown wire from the luminaire to the supply live wire (red or brown). Connect the blue wire to the supply neutral wire (black or blue). Connect the green/yellow wire to the supply earth wire (green/yellow) or connect the supply earth to the luminaire earth terminal marked: 



4 CLASS II Luminaires (Not earthed) - These luminaires are double insulated and have the symbol:  These fittings do not have to be connected to the supply earth. Make sure that the basic insulation of the supply wiring cannot contact touchable metal. Connect the brown wire from the luminaire to the supply live wire (red or brown). Connect the blue wire to the supply neutral wire (black or blue). Isolate the supply earth wire.

If silicone sleeving is provided, fit terminal block or lamp holder, to protect cable from heat.



over the supply cable up to the at least the mounting surface, to