

NC DWELL

SPECIFICATION

Product model	NC-003328	
Product Size (mm)	202*55*130	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	/
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	1.04 Kg
	Rated Power	18 W
	LED Module Rated Power	1W*16
	Input Voltage	100-240V~
	Frequency Range	50/60Hz
	Luminaire luminous efficiency(EFF)	88 lm/W
	Imax(cd)	7912 cd
	Luminaire Efficiency(LOR%)	86
	Total Flux	1663 lm
	Beam angle(At 50% of Imax)	14°
	Energy Efficiency Index(EEI)	1.16
	Colour rendering index(Ra)	≥80
Colour Temperature(CCT)	3000 K	
SDCM	≤5	
Surge transient protection	/	
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	OSRAM
	LED Model No.	3030
	LED Nominal Flux(lm)	120 lm
	LED Quantity	16 PCS
Driver	STOCK NUMBER	L-QD-PA148
	Driver Output	30-50VDC
	Driver Efficiency	≥83%
	Power Factor	≥0.85
	THD	≤10%
	Ripple current	≤15%
Certification	CE, CCC, CB, EAC, SAA, BIS	

