

NC DWELL

SPECIFICATION

Product model	NC-003731	
Product Size (mm)	172*Φ64*279 mm	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	0.37 Kg
	Rated Power	5 W
	LED Module Rated Power	1W*4
	Input Voltage	220V
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	68 lm/W
	I_{max}(cd)	3007 cd
	Luminaire Efficiency(LOR%)	78
	Total Flux	346 lm
	Beam angle(At 50% of I_{max})	15°
	Energy Efficiency Index(EEI)	0.32
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000K
SDCM	≤5	
Surge transient protection	/	
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	OSRAM
	LED Model No.	3030
	LED Nominal Flux(lm)	120 lm
	LED Quantity	4
Driver	STOCK NUMBER	L-QD-PA107
	Driver Output	8-12VDC
	Driver Efficiency	≥68%
	Power Factor	≥0.45
	THD	/
	Ripple current	≤30%
Certification	CE, CCC, CB, EAC, SAA, BIS	

