

NC DWELL

SPECIFICATION

Product model	NC-003333	
Product Size (mm)	110*70*76mm	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	/
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	0.46 Kg
	Rated Power	3.5W
	LED Module Rated Power	3W*1
	Input Voltage	220V
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	81 lm/W
	Imax(cd)	210 cd
	Luminaire Efficiency(LOR%)	77
	Total Flux	279 lm
	Beam angle(At 50% of Imax)	67°
	Energy Efficiency Index(EEI)	0.10
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000K
	SDCM	≤5
	Surge transient protection	/
Working temperature	-30°C ~ +45°C	
LED Chip	LED Brand	SEOUL
	LED Model No.	5050
	LED Nominal Flux(lm)	360 lm
	LED Quantity	1
Driver	STOCK NUMBER	L-QD-PA145
	Driver Output	18-27VDC
	Driver Efficiency	≥72%
	Power Factor	≥0.45
	THD	/
	Ripple current	≤30%
Certification	CE, CCC, CB, EAC, SAA, BIS	

